

## DATA SHEET

### 20V Cordless Framing Nailer LD34100

LD34100							
	FEATURES						
	<ul style="list-style-type: none"> <li>✓ Brushless motor technology</li> <li>✓ Select fire mode button</li> <li>✓ Adjustable nail depth</li> <li>✓ Belt hook</li> <li>✓ Drives up to 750 nails/charge</li> <li>✓ Plastic carrying case included</li> <li>✓ Makita, Dewalt &amp; Milwaukee battery adaptor included</li> </ul>						
	APPLICATIONS						
	<ul style="list-style-type: none"> <li>• Floor and wall framing</li> <li>• Window build-up</li> <li>• Wall sheathing</li> <li>• Roofing</li> </ul>						
SPECIFICATIONS							
Weight (w/o battery)	4.2 kg						
Dimensions (w/o battery)	370 x 340 x 131 mm						
Load capacity	50 nails						
Firing speed	Up to 90 nails/min						
Recommended pressure range	5~8 bar (adjustable through air valve)						
Actuation mode	Contact/sequential actuation						
Battery	20V 4.0Ah battery & 2A charger – <b><u>Not included!</u></b>						
Impact power	100~120J						
FASTENERS							
 <p><b>Paper collation</b></p>	34° paper tape collated strip nails						
	<table border="0" style="width: 100%;"> <tr> <td style="width: 30%;">Length</td> <td>50~100 mm (Ring shank up to 100 mm in soft wood)</td> </tr> <tr> <td>Shank</td> <td>2.87~3.76 mm</td> </tr> <tr> <td>Head</td> <td>6.8~7.2 mm</td> </tr> </table>	Length	50~100 mm (Ring shank up to 100 mm in soft wood)	Shank	2.87~3.76 mm	Head	6.8~7.2 mm
Length	50~100 mm (Ring shank up to 100 mm in soft wood)						
Shank	2.87~3.76 mm						
Head	6.8~7.2 mm						