


DATASHEET

Framing nailer SRN9021

SRN9021 Framing nailer											
	FEATURES <ul style="list-style-type: none"> * Powerful * Big load capacity * Comfortable rubber grip 										
	APPLICATIONS <ul style="list-style-type: none"> * Floor and wall framing * Window build-up * Wall sheathing * Roofing 										
SPECIFICATIONS											
Weight Dimensions Load capacity Maximum allowable pressure Recommended pressure range Actuation mode	3.59 kg 554 x 108 x 340 mm 64~70 nails 8.3bar 5bar to 7bar Contact /Sequential actuation										
FASTENERS											
<table border="0"> <tr> <td> Shank Type Smooth Screw Ring </td> <td> Nail Length 50mm 90mm </td> <td> Shank Diameter 2.87mm ~ 3.33mm </td> <td> Head Diameter 5.8mm ~ 7.2mm </td> </tr> </table>	Shank Type Smooth Screw Ring	Nail Length 50mm 90mm	Shank Diameter 2.87mm ~ 3.33mm	Head Diameter 5.8mm ~ 7.2mm	21° plastic collated strip nails <table border="0"> <tr> <td>Length</td> <td>50~90 mm</td> </tr> <tr> <td>Shank</td> <td>2.8~3.33 mm</td> </tr> <tr> <td>Head</td> <td>5.8~7.2 mm</td> </tr> </table>	Length	50~90 mm	Shank	2.8~3.33 mm	Head	5.8~7.2 mm
Shank Type Smooth Screw Ring	Nail Length 50mm 90mm	Shank Diameter 2.87mm ~ 3.33mm	Head Diameter 5.8mm ~ 7.2mm								
Length	50~90 mm										
Shank	2.8~3.33 mm										
Head	5.8~7.2 mm										